

Concrete Lifting Clutches

SwiftLift Concrete Lifting Clutches have been exclusively designed and approved for use with Reid SwiftLift Anchors.

They are available in a range of Working Load Limits.

They have been designed so that they cannot spontaneously disengage whilst the system is under load at any orientation, provided they are connected to the head of the correct anchor in the recess. When the lift is complete and the load released, the clutch is quickly and simply disengaged.

Identification markings are required for the SwiftLift™ Lifting Eye to comply with AS 3850 – 2003.

The SwiftLift™ Lifting Eye must be proof load tested every 12 months in accordance with AS 3850–2003.

The SwiftLift™ Lifting Eye has a FOS (factor of safety) of no less than 5 in accordance with AS 3850 – 2003.



Product Specifications

Name	ITEM #	WLL (tonnes)	Weight (kg)
Concrete Lifting Clutch (Eye) Swiftlift 1.3t	15559	1.3	0.9
Concrete Lifting Clutch (Eye) Swiftlift 2.5t	14488	2.5	1.3
Concrete Lifting Clutch (Eye) Swiftlift 5t	17268	5	3.2
Concrete Lifting Clutch Swiftlift 7t	12246	7	7.3
Concrete Lifting Clutch (Eye) Swiftlift 10t	15724	10	10
Concrete Lifting Clutch (Eye) Swiftlift 20t	13239	20	20.4

Uncontrolled version printed 28-Nov-2021 .See www.nobles.com.au for latest up-to-date product information.