




G100 AW Master Links

The AW Master Link is ideally suited for pewag Connex Connecting Links and may be used for Single leg or Two leg chain slings.

The flattened section enables universal connecting options and links are manufactured according to EN 1677-4 and Australian Standards with mechanical values for Grade 100.

* Warning! - Incompatible chain sling components may create a hazard by improperly functioning or failing in service (refer AS3775.2-2014 clause 6.3). Before use, a competent person shall ensure that all chain slings and components (including the shorteners) are compatible and that they fit properly without overcrowding. If in doubt – please consult A. Noble & Son Ltd. for advice before proceeding.



Product Specifications

Name	ITEM #	Suits Chain Size (mm) 1 Leg	Suits Chain Size (mm) 2 Leg	WLL @ 90 Deg (tonnes)	t (mm)	w (mm)	s (mm)	d (mm)	Weight (kg)
Master Link 2.4T 6mm Gr100 Pewag AW13	30577	6+7	6	2.3	110	60	10	13	0.34
Master Link 3.3T 8mm - 7mm Gr100 Pewag AW16	30578	8	7	3.5	110	60	14	16	0.53
Master Link 4.3T 10mm - 8mm Gr100 Pewag AW18	30579	10	8	5	135	75	14	19	0.92
Master Link 6.9T 13mm - 10mm Gr100 Pewag AW22	30580	13	10	7.6	160	90	17	23	1.6
Master Link 11.6T 16mm - 13mm Gr100 Pewag AW26	30581	16	13	10	180	100	20	27	2.46
Master Link 17.3T 19mm - 16mm Gr100 Pewag AW32	30582	19	16	14	200	110	26	33	4.14
Master Link 24.2T 22mm - 19mm Gr100 Pewag AW36	30583	22	19	25.1	260	140	0	36	6.22
Master Link 32.9T 26mm - 22mm Gr100 Pewag AW45	30584	26	22	30.8	340	180	0	45	12.82
Master Link 45.8T 32mm - 26mm Gr100 Pewag AW50	30585	32	26	40	350	190	0	50	16.55
Master Link 69.2T 32mm Gr100 Pewag AW56	30586		32	64	400	200	0	56	27.01